SERVICE HARLEY-DAVIDSON BULLETIN

No. 597

September 16, 1969

IMPORTANT TIRE INFORMATION / 1970 SPORTSTER

Special Goodyear tires and rims are supplied as original equipment on standard 1970 Sportster (high ground clearance) models. The tires are identified on the tire sidewall as follows:

> Front - 3, 75 x 19 Sport Rib Rear - 4. 25 x 18 All Traction


These tires must be used exclusively for replacement on these rims. This type rim has a special tapered bead seat with a safety hump as shown in sketch below. Standard tires such as Goodyear 3, 50 x 18, 4, 00 x 18 or 3, 25/3, 50 x 19 sizes will not fit correctly and will result in unsafe operation if installed for any reason.

Correct inner tubes for use with tires are identified as follows:

Front - 3. 25 x 18, 3. 50 x 19 Rear - 4.00 x 18, 4.50 x 19

Taper Bead Seat Safety Hump

Rim Shape for size 3.75 x 19 and 4, 25 x 18 tires (standard sizes used for 1970 - high ground clearance models)



Rim shape for 3.50 x 18, 4.00 x 18, 3. 25/3. 50 x 19 tires (size 3. 50 x 19 is used for 1970 low ground clearance models)

New "C-Section" rims can be positively identified after tire is removed from rim by the following part numbers stamped in rim.

Steel Rims:

Propt ... 43003-70/19 x 2,50C

Rear :.. 43004-70/18 x 2.30C

Alaminum Rims: Front... 43010-70/2.50C-19

Rear ... 43008-70/2,50C-18

HARLEY-DAVIDSON MOTOR CO., INC.